

CENTRE FOR DEVELOPMENT OF IMAGING TECHNOLOGY (C-DIT)

Chitranjali Hills, Thiruvallam, Thiruvananthapuram-27

Phone: 0471-2380910, 912 Fax: 0471- 2380681

Ref. No. C-DIT/DIGI/17-18/T103

Date: 13.03.2018

TENDER NOTICE

SUPPLY OF DIGITAL SLR CAMERA

Sealed tenders are invited for the supply of Digital SLR Camera. The envelopes containing the tender should bear the superscription ***“Tender for the supply of Digital SLR Camera “*** and should be addressed to The Registrar, Centre for Development of Imaging Technology (C-DIT), Chitranjali hills, Thiruvallam, Thiruvananthapuram 695027. Intending tenderers may submit the tenders on their own papers by post/hand. Last date for receipt of tenders is **23.03. 2018, 3.00 PM.** Late tenders will not be accepted. The tenders will be opened at **3.30 PM on 23. 03. 2017** in C-DIT office in the presence of the tenderers or their authorized representatives who may be present at that time. Details of the requirements and the conditions governing the supply can be downloaded from our website www.cdit.org

Thiruvananthapuram

13.03.2018

Sd/-

REGISTRAR

CENTRE FOR DEVELOPMENT OF IMAGING TECHNOLOGY (C-DIT)

Chitranjali Hills, Thiruvallam, Thiruvananthapuram-27

Phone: 0471-2380910, 912 Fax: 0471- 2380681

Ref. No. C-DIT/DIGI/17-18/T103

Date: 13.03.2018

TENDER FOR SUPPLY OF DIGITAL SLR CAMERA

Digital SLR Camera – Requirement 2 Nos

SPECIFICATION

Type	Digital, single-lens reflex, AF / AE camera	
Recording Media	CF card (Type I, UDMA mode 7-compatible), SD memory card, SDHC memory card, SDXC memory card	
Image sensor size	Approx. 36 x 24mm	
Image Sensor		
Type	CMOS sensor	
Effective Pixels	Approx. 22.30 megapixels	
Aspect Ratio	3:2	
Dust Delete Feature	Auto, Manual, Dust Delete Data appending	
Recording System		
Recording Format	Design rule for Camera File System 2.0	
Image Type	JPEG, RAW (14-bit Canon original), RAW + JPEG simultaneous recording enabled	
Recording Pixels	L (Large):	Approx. 22.10 megapixels (5760 x 3840)
	M (Medium):	Approx. 9.80 megapixels (3840 x 2560)
	S1 (Small 1):	Approx. 5.50 megapixels (2880 x 1920)
	S2 (Small 2):	Approx. 2.50 megapixels (1920 x 1280)
	S3 (Small 3):	Approx. 350,000 pixels (720 x 480)
	RAW:	Approx. 22.10 megapixels (5760 x 3840)
	M-RAW:	Approx. 10.50 megapixels (3960 x 2640)
	S-RAW:	Approx. 5.50 megapixels (2880 x 1920)
Recording function	Standard, Auto switch card, Rec. separately, Rec. to multiple	
Create / Select a Folder	To be provided	
File name	Preset code, User setting 1, User setting 2	
File numbering	Continuous, auto reset, manual reset	

Image Processing During Shooting	
Picture Style	Auto, Standard, Portrait, Landscape, Neutral, Faithful, Monochrome, User Def. 1 - 3
White Balance	Auto, Preset (Daylight, Shade, Cloudy, Tungsten light, White fluorescent light, Flash), Custom, Colour temperature setting (Approx. 2500 - 10000K), White balance correction, and White balance bracketing is to provided
Noise Reduction	Applicable to long exposures and high ISO speed shots
Automatic Image Brightness Correction	Auto Lighting Optimizer
Highlight Tone Priority	To be Provided
Lens Peripheral Illumination Correction	Peripheral illumination correction, Chromatic aberration correction
Viewfinder	
Type	Eye-level pentaprism
Coverage	Vertical / Horizontal Approx. 100% (with Eye point Approx. 21mm)
Magnification	Approx. 0.71x (-1m ⁻¹ with 50mm lens at infinity)
Eyepoint	Approx. 21mm (from eyepiece lens center at -1m ⁻¹)
Build-in Dioptic adjustment	Approx. -3.0 - +1.0m ⁻¹ (dpt)
Focusing Screen	Fixed
AF status indicator	To be Provided
Grid display	To be Provided
Electronic level	Horizontal: 1° increments, ±6°
	Vertical: 1° increments, ±4°
	* During horizontal shooting
Mirror	Quick-return type
Depth-of-field Preview	To be Provided
Autofocus	
Type	TTL secondary image-registration, phase detection
AF Points	61 points (Up to 41 cross-type points) * Number of available AF points and cross-type points vary depending on the lens.
Focusing Brightness Range	EV -2 - 18 (with center f/2.8 AF point, 23°C / 73°F, ISO 100)
Focusing Modes	One-Shot AF, AI Servo AF, AI Focus AF, Manual focusing (MF)
AF Area Selection Modes	Single-point Spot AF (manual selection), Single-point AF (manual selection), AF point expansion (manual selection; up, down, left, and right), AF point expansion (manual selection; surround),

	Zone AF (manual selection), Auto selection of 61 AF points	
AF Configuration Tool	Case 1 - 6	
AI Servo Characteristics	Tracking sensitivity, Acceleration / deceleration tracking, AF point auto switching	
AF Fine Adjustment	AF Micro adjustment (All lenses by same amount or Adjust by lens)	
AF-assist Beam	Emitted by the EOS-dedicated external Speedlite	
Exposure Control		
Metering Modes	63-zone TTL full-aperture metering	
	<ul style="list-style-type: none"> • Evaluative metering (linked to all AF points) • Partial metering (Approx. 6.2% of viewfinder at center) • Spot metering (Approx. 1.5% of viewfinder at center) • Center-weighted average metering 	
Metering Range	EV 1 - 20 (at 23°C / 73°F with EF50mm f/1.4 USM lens, ISO 100)	
Exposure Control	Program AE (Scene Intelligent Auto, Program), Shutter-priority AE, Aperture-priority AE, Manual exposure, Bulb exposure	
ISO Speed (Recommended exposure index)	Scene Intelligent Auto: ISO 100 - 12800 set automatically P, Tv, Av, M, B: Auto ISO, ISO 100 - 25600 (in 1/3- or whole-stop increments), or ISO expansion to L (50), H1 (equivalent to ISO 51200), H2 (equivalent to ISO 102400)	
ISO Speed Settings	ISO speed range, Auto ISO range, and Auto ISO minimum shutter speed settable	
Exposure Compensation	Manual:	±5 stops in 1/3- or 1/2-stop increments
	AEB:	±3 stops in 1/3- or 1/2-stop increments (Can be combined with manual exposure compensation)
AE Lock	Auto:	Applied in One-Shot AF mode with evaluative metering when focus is achieved
	Manual:	By AE lock button
HDR Shooting		
Dynamic Range Adjustment	Auto, ±1 EV, ±2 EV, ±3 EV	
Effect	Natural, Art standard, Art vivid, Art bold, Art embossed	
Auto Image Align	To be provided	
Multiple Exposures		
Shooting Method	Function / control priority, Continuous shooting priority	
No. of Multiple Exposures	2 to 9 exposures	
Multiple-Exposure Control	Additive, Average, Bright, Dark	

Shutter		
Type	Electronically-controlled, focal-plane shutter	
Shutter Speeds	1/8000sec. to 1/60sec. (Scene Intelligent Auto mode), X-sync at 1/200sec. * With a wide-angle lens, the shutter speed may be 1/60sec. or slower. 1/8000sec. to 30secs., bulb (Total shutter speed range. Available range varies by shooting mode.)	
Drive System		
Drive Modes	Single shooting, High-speed continuous shooting, Low-speed continuous shooting, Silent single shooting, Silent continuous shooting, 10secs. self-timer / remote control, 2secs. self-timer / remote control	
Continuous Shooting Speed	High-speed continuous shooting:	Max. Approx. 6 shots/sec.
	Low-speed continuous shooting:	Max. Approx. 3 shots/sec.
	Silent continuous shooting:	Max. Approx. 3 shots/sec.
Max. Burst	JPEG Large / Fine:	Approx. 65 shots (Approx. 16270 shots)
	RAW:	Approx. 13 shots (Approx. 18 shots)
	RAW + JPEG Large / Fine:	Approx. 7 shots (Approx. 7 shots)
	* Figures are based on Canon's testing standards (ISO 100 and Standard Picture Style) and a 8GB card. * Figures in parentheses apply to an UDMA mode 7, 128GB card based on Canon's testing standards.	
External Speedlite		
Compatible Speedlites	EX-series Speedlites	
Flash Metering	E-TTL II autoflash	
Flash Exposure Compensation	±3 stops in 1/3- or 1/2-stop increments	
FE Lock	To be Provided	
PC Terminal	To be Provided	
External Speedlite control	To be Provided	
	To be Compatible with radio wireless flash photography.	
Live View Shooting		
Shooting Modes	3:2, 4:3, 16:9, 1:1	
Focusing Modes	Live mode, Face detection Live mode (contrast detection), Quick mode (phase-difference detection), Manual focusing (Approx. 5x	

	/ 10x magnification possible)	
Focusing brightness range	EV 1 - 18 (with contrast detection, at 23°C / 73°F, ISO 100)	
Metering Modes	Evaluative metering with the image sensor	
Metering Range	EV 0 - 20 (at 23°C / 73°F with EF50mm f/1.4 USM lens, ISO 100)	
Silent Shooting	To be Provided	
Three Types	Three types	
Movie Shooting		
Movie Recording Compression	MPEG-4 AVC / H.264 Variable (average) bit rate	
Audio Recording Format	Linear PCM	
Recording Format	MOV	
Recording Size And Frame Rate	1920 x 1080 (Full HD):	30p / 25p / 24p
	1280 x 720 (HD):	60p / 50p
	640 x 480 (SD):	30p / 25p
	* 30p: 29.97fps, 25p: 25.00fps, 24p: 23.976fps, 60p: 59.94fps, 50p: 50.00fps	
Compression Method	ALL-I (I-only), IPB	
File size	1920 x 1080 (30p / 25p / 24p) / IPB:	Approx. 235MB/min.
	1920 x 1080 (30p / 25p / 24p) / ALL-I :	Approx. 685MB/min.
	1280 x 720 (60p / 50p) / IPB:	Approx. 205MB/min.
	1280 x 720 (60p / 50p) / ALL-I:	Approx. 610MB/min.
	640 x 480 (30p / 25p) / IPB:	Approx. 78MB/min.
	* Card reading / writing speed necessary for movie shooting: CF card: IPB: at least 10MB per sec. / ALL-I: at least 30MB per sec. SD card: IPB: at least 6MB per sec. / ALL-I: at least 20MB per sec.	
Focus Modes	Same as focusing with Live View shooting	
Metering Modes	Center-weighted average and Evaluative metering with the image sensor * Automatically set by the focusing mode.	
Metering Range	EV 0 - 20 (at 23°C / 73°F with EF50mm f/1.4 USM lens, ISO 100)	

Exposure Control	1. Auto exposure, 2. Shutter-priority AE, 3. Aperture-priority AE, 4. Manual exposure * With 1, 2, and 3, exposure compensation and AE lock are possible (except in Scene Intelligent Auto mode).
Exposure compensation	±3 stops in 1/3-stop increments (±5 stops for still photos)
ISO speed (Recommended exposure index)	Scene Intelligent Auto and Tv: Automatically set within ISO 100 - 12800 P, Av, and B: Automatically set within ISO 100 - 12800 expandable to H (equivalent to ISO 25600) M: Auto ISO (automatically set within ISO 100 - 12800), ISO 100 - 12800 set manually (in 1/3- or whole-stop increments), expandable to H (equivalent to ISO 16000 / 20000 / 25600)
Time Code	To be Supported
Drop Frames	Compatible with 60p / 30p
Sound Recording	Built-in monaural microphone, external stereo microphone terminal provided Sound recording level adjustable, wind filter provided
Headphones	Headphone terminal to be provided
Grid Display	Three types
Still Photos	To be provided
LCD Monitor	
Type	TFT colour, liquid-crystal monitor
Monitor Size and Dots	Wide, 8.1 cm (3.2-in.) (3:2) with Approx. 1.04 million dots
Brightness Adjustment	Auto (Dark, Standard, Bright), Manual (7 levels)
Electronic Level	Horizontal: 1° increments, ±6°
	Vertical: 1° increments, ±4°
Interface Languages	25
Feature Guide	Displayable
Playback	
Image Display Formats	Single image display, Single image + Info display (Basic info, shooting info, histogram), 4-image index, 9-image index, 2-image display
Highlight Alert	Overexposed highlights blink
AF Point Display	Possible
Grid Display	Three types
Zoom Magnification	Approx. 1.5x - 10x, starting magnification and position settable
Image Browsing Methods	Single image, jump by 10 or 100 images, by shooting date, by folder, by movies, by stills, by rating
Image Rotate	To be provided
Ratings	To be provided

Movie Playback	Enabled (LCD monitor, video / audio OUT, HDMI OUT), built-in speaker
Slide Show	All images, by date, by folder, movies, stills, or by rating
Image protect:	To be provided
Copying images	To be provided
Post-Processing of Images	
In-camera RAW Image Processing	Brightness correction, White balance, Picture Style, Auto Lighting Optimizer, High ISO speed noise reduction, JPEG image-recording quality, Colour space, Peripheral illumination correction, Distortion correction, and Chromatic aberration correction
Resize	To be provided
Direct Printing	
Compatible Printers	PictBridge-compatible printers
Printable Images	JPEG and RAW images
Print Ordering	DPOF Version 1.1 compatible
Image Transfer	
Transferrable Images	Still photos (JPEG, RAW, RAW + JPEG images), Movies
Custom Functions	
My Menu Registration	To be provided
Custom Shooting Modes	Register under Mode Dial's C1 / C2 / C3
Copyright Information	Entry and inclusion enabled
Interface	
Audio / Video OUT/ Digital Terminal	Analog video (Compatible with NTSC / PAL) / stereo audio output Personal computer communication, Direct printing (Hi-Speed USB or equivalent), Wireless File Transmitter WFT-E7, GPS Receiver GP-E2 connection
HDMI mini OUT terminal	Type C (Auto switching of resolution), CEC-compatible
External Microphone IN Terminal	3.5mm stereo mini-jack
Headphone terminal	3.5mm stereo mini-jack
Remote Control Terminal	Compatible with N3-type remote controller
Wireless Remote Control	Remote Controller RC-6
Eye-Fi card	Compatible
Power	
Battery	Battery Pack LP-E6 (Quantity 1) * AC power can be supplied via AC Adapter Kit ACK-E6.

	* With Battery Grip BG-E11 attached, size-AA/LR6 batteries can be used.	
Battery Information	Remaining capacity, Shutter count, Recharge performance, and Battery registration possible	
Battery Life (Based on CIPA testing standards)	With viewfinder shooting:	Approx. 950 shots at 23°C / 73°F, Approx. 850 shots at 0°C / 32°F
	With Live View shooting:	Approx. 200 shots at 23°C / 73°F, Approx. 180 shots at 0°C / 32°F
Movie Shooting Time	Approx. 1hr. 30mins. at 23°C / 73°F Approx. 1hr. 20mins. at 0°C / 32°F (with fully-charged Battery Pack LP-E6)	
Date / Time Battery	CR1616 lithium battery (Quantity 1)	
Operating Environment		
Working Temperature Range	0°C - 40°C / 32°F - 104°F	
Working Humidity	85% or less	
Battery Pack LP-E6		
Type	Rechargeable lithium-ion battery	
Rated Voltage	7.2 V DC	
Battery Capacity	1800 mAh	
Battery Charger LC-E6		
Compatible Battery	Battery Pack LP-E6	
Recharging Time	Approx. 2hrs. 30mins.	
Lens		
Angle of View	Diagonal extent:	84° - 23°20'
	Horizontal extent:	74° - 19°20'
	Vertical extent:	53° - 13°
Lens Construction	18 elements in 13 groups	
Minimum Aperture	f/22	
Closest Focusing Distance	0.45m / 1.48ft. (from image sensor plane)	
Max. Magnification	0.23x (at 105mm)	
Field of View	535 x 345 - 158 x 106mm / 21.1 x 13.6 - 6.2 x 4.2in. (at 0.45m)	
Image Stabilizer	Lens shift type	
Filter Size	77mm	

TENDER FOR SUPPLY OF DIGITAL SLR CAMERA

GENERAL TERMS AND CONDITIONS

1. This Tender is invited for the "**supply pf Digital SLR Camera**" for one of the projects taken up by C-DIT.
2. C-DIT reserves the right to cancel any or all tenders without assigning any reason whatsoever

3. ELIGIBILITY CRITERIA OF TENDERER

To qualify for award of the work, the intending tenderer must be an authorized dealer / supplier of the quoted items/ with prior experience in supplying the same or similar equipments in the last two years.

4. The Tenderers are responsible for effecting supply to the entire satisfaction of the undersigned or his authorized representatives. In case any defect in the item supplied is noticed, such item will be rejected at the risk and cost of the Supplier.
5. Tenders shall invariably be accompanied by manufacturer's catalogues and leaflets giving full specifications. Technical particulars and other details of the items offered 'brand make' and complete specification should be mentioned in the tender. In the absence of full details and technical specification the tenders for the items will be rejected.
6. The undersigned does not bind himself to accept the lowest tender and reserve himself the rights of accepting the whole or any part of the tender and the tenderer shall be bound to supply the accepted item at the rates quoted.
7. No advance payment will be made against supplies.
8. The rate quoted by the Tenderer shall be inclusive of the transportation charges, installation charges and unloading charges at site. Rates quoted by the tenderer shall be valid for a period of six months from the date of opening of the tender.
9. Delivery period shall be specifically indicated in the tender and strictly adhered to. The supply shall be arranged within 15 days on receipt of the firm order.

Any delay in the delivery period after the supply order is placed may result in cancellation of the supply order.

10. The rate should be quoted for the unit shown in the list and tenders which do not indicate this essential information will not be considered.
11. There is no separate bid form. The supplier shall submit the price offers in their own paper
12. The rate quoted for material shall be final and no enhancement will be allowed under any circumstances.
13. The Supplier/ Contractor shall provide on-site comprehensive warranty of **one year** for the products from the date of supply.
14. If the tenderer furnishes wrong and/or misleading data, statement(s) etc. about technical acceptability of the goods and services offered by it, its tender will be liable to be ignored and rejected in addition to other remedies available to the purchaser in this regard.
15. After Sales Service: After sales service centre should be available in Thiruvananthapuram. Complaints should be attended properly, maximum within 24 hrs. The service should be provided directly by Tenderer.
16. All items offered shall conform in all respects to the relevant Indian standard Specification with up to date amendments wherever applicable.
17. Any dispute / differences between the parties arising out of and in connection with the contract shall be settled amicably by mutual negotiations. Unresolved disputes/ differences, if any, shall be settled by Arbitration and the arbitration proceedings shall be conducted at Thiruvananthapuram (India) in English language, under the Indian Arbitration and Conciliation Act, 1996. Unsettled disputes will be referred to courts and courts in Thiruvananthapuram/ Kerala will have exclusive jurisdiction over the same.

18. PAYMENT TERMS

The following terms of payment shall be applicable for the contract

100 % payment against successful supply of the Equipment.

19. Agreement: The Successful bidder within 7 days of getting confirmed purchase order has to enter an agreement with C-DIT in Rs.200 worth non judicial stamp paper, to ensure warranty and after sales support during the warranty period.

20. Authority: The authority for the acceptance of the tenders rests exclusively with the C-DIT. The C-DIT does not undertake to accept the lowest or any particular tender or to assign any reason whatsoever for the rejection of any tender.

21. The last date for submission of tender 23.03.8 3.00 PM The tender will be opened on the same day at 3.30 PM

22. At any time prior to the deadline for submission of tenders, the C-DIT may, for any reason deemed fit by it, modify/amend the tender documents by issuing suitable amendment(s)/ corrigendum's to it. Corrigendum to this tender shall be published in the site www.cdit.org. Prospective bidders are advised to regularly visit the website: www.cdit.org to keep track of corrigendum, if any.

23. In case of doubt:

If the bidder has any doubt on technical specifications or on terms & conditions stipulated above, please contact Smt. Deepa N, Head, Digitization Department in Mobile Number: 9895788220

Sd/
REGISTRAR, C-DIT
Dated 13.03.2018

PROFORMA OF "AGREEMENT"

(To be executed on non-Judicial Stamp Paper)

This Agreement made this. day of Two thousand and Between Centre for Development of Imaging Technology, a Society, registered under the Travancore-Cochin Literary, Scientific and Charitable Societies Registration Act XII of 1955, having its registered Office at Chitranjali Hills, Thiruvallom, Trivandrum 695 027 (hereinafter referred to as "C-DIT" which expression shall include its administrators, successors, executors and assigns) of the one part and a company/firm incorporated under the.. having its registered Office at (hereinafter referred to as the "Contractor" or "X" (brief name of contracting Co.) (which expression shall include its administrators, successors, executors and permitted assigns) of the other part.

WHEREAS C-DIT has invited bids for (briefly describe scope of the (work) as per its specification Ref. No.

AND WHEREAS..... "X" had participated in the above referred bidding vide their proposal No. dated and C-DIT accepted their aforesaid proposal and awarded the dated and C-DIT accepted their aforesaid proposal and awarded the contract to. "X" on terms and conditions contained in its letter of Indent/Purchase Order No. dated And the documents referred to therein, which have been accepted by "X" resulting into a "Contract"

NOW THEREFORE THIS DEED WITNESSETH AS UNDER :-

Article 1.0 AWARD OF CONTRACT

C-DIT has awarded the contract to “X” for the work of on the terms and conditions contained in its letter of Indent/Purchase Order No. dated and the documents referred to therein. The award has taken effect from.i.e. the date of issue of the aforesaid Letter. The terms & expressions used in this Agreement shall have the same meaning as are assigned to them in the “Contract Documents” referred to in the succeeding Article.

Article 2.0 CONTRACT DOCUMENTS

The Contract shall be performed strictly as per the terms and conditions stipulated herein and in the following documents attached herewith (hereinafter referred to as “Contract Documents”).

Article 3.0 CONDITIONS & CONVENANTS

The scope of Contract, Consideration, Terms of payment, price Adjustment, Taxes wherever applicable, Insurance, liquidated Damages, performance, Guarantee and all other terms and conditions are contained in C-DIT’s Purchase Order No. dated read in conjunction with other aforesaid Contract documents. The Contract shall be only performed by the Contractor strictly and faithfully in accordance with the terms of the Agreement.

The scope of work shall also include supply and installation of all such items which are not specifically mentioned in the contract Documents, but which are needed for successful, efficient, safe & reliable operation of the equipment unless otherwise specifically excluded in the specifications under “exclusions” or Purchase Order.

TIME SCHEDULE: Time is the essence of the contract and schedules shall be strictly adhered to. “X” shall perform the work in accordance with the agreed schedule as given in letter of Indent/Purchase Order.

The Contractor guarantees that the equipment package under the contract shall meet the ratings and performance parameters, as stipulated in the Technical Specifications (Volume II) and in the event of any deficiencies found in the requisite performance figures, the C-DIT may at its option reject the equipment package or alternatively accept it on the terms and conditions and subject to levy of the liquidated damages in terms of Contract Documents. The amount of liquidated damages so leviable shall be in accordance with the Contract Documents and without any limitation.

It is further agreed by the Contractor that the Contract performance Guarantee shall in no way be construed to limit or restrict the C-DIT's right to recover the damages/compensation due to short-fall in the equipment performance figures as stated in Para 3.4 above or under any other clause of the Agreement. The amount of damages/Compensation shall be recoverable either by way of deduction from the contract price, contract performance guarantee and/or otherwise.

The Contract performance Guarantee furnished by the Contractor is irrevocable and un-conditional and the C-DIT shall have the powers to invoke it notwithstanding any dispute or difference between the C-DIT and the contractor pending before any court, tribunal, arbitrator or any other authority.

This Agreement constitutes full and complete understanding between the parties and terms of the presents. It shall supersede all prior correspondence to the extent of inconsistency of repugnancy to the terms and conditions contained in the Agreement. Any modification of the Agreement shall be effected only by a written instrument signed by the authorized representatives of both the parties.

Article 4.0 SETTLEMENTS OF DISPUTES

It is specifically agreed by and between the parties that all the differences or disputes arising out of the Agreement or touching the subject matter of the Agreement shall be decided by process of settlement & Arbitration as specified in clauses and provisions of the Arbitration and Conciliation Act 1996 and Kerala Courts alone shall have exclusive jurisdiction over the same.

NOTICE OF DEFAULT

Notice of default given by either party to the other party under the Agreement shall be in writing and shall be deemed to have been duly and properly served upon the parties here to if delivered through official email or by registered post with acknowledgement due addressed to the signatories

IN WITNESS WHEREOF, the parties through their duly authorized representatives have executed these presents (execution where of has been approved by the competent authorities of both the parties) on the day, month and year first above mentioned at Trivandrum.

WITNESS

C-DIT

1.

(Signature)
(Name)

2.

(Designation)
(Seal)

1.

(Contractors signature)
(Designation)
(Seal)

2.